



Enter Search Keyword

Product Category

HVAC Parts

Commercial Refrigeration

Test Instruments and Alarms

Tools and Chemicals

Air Conditioning Equipment

Appliance Parts

- Dishwasher Parts


- Dryer Parts

- Range Parts

- Refrigerator Parts

- Washer Parts

About Us Distributors Contact Us Track Your Order New Products



Hover over picture to Zoom
Click to enlarge

61100N
61100N--WALL THERMOSTAT

For Conventional Systems and Single Stage Heat Pumps. Professional Series CTC thermostats feature attractive styling, overheat protection and static protection.

Features/Benefits

- English / Spanish Packaging and Instruction Card
- Gas / Electric Fan Switch
- F° / C° Switch
- Front Access Reset Button
- Low Battery Indication
- Separate O & B Terminals
- Compressor Short Cycle Protection
- Permanent Memory Retains Settings
- Hardwire or Battery Powered
- 1.5 Square Inch Display with Bright Blue Backlight

Locate a Distributor Near You

Specifications Applications Downloads Cross Reference Accessories

Operating Humidity:	5% to 95% Relative Humidity
Storage Temperature:	14°F to 140°F (-10°C to 60°C)
Accuracy:	± 1°F (± .5°C)
Display Range:	40°F to 99°F (5°C to 37°C)
Control Range:	45°F to 90°F (7°C to 32°C)
DC Power:	3.0 Volts DC (2 AA Alkaline Batteries Included)
AC Power:	18-30 Volt AC
Electric Rating:	24 Volt AC (18-30 Volt AC) 1 Amp Maximum Load per Terminal, 3 Amp Total Maximum Load (All Terminals)
Dimensions:	3.62" x 4.72" x 1.38"
Terminations:	Rc, Rh, B, O, Y1, W1, G, C



Appliance Replacement Parts Distributors

2014 SUPPLEMENT



2014 Supplement



HVAC/R & Test Instrument Catalog



Surge Protectors Warranty Registration Site



AHR Expo Mexico
September 23-25 2014
Centro Banamex, Mexico
D.F.

