

CEILING RADIATION FIRE DAMPERS

Horizontal/Rectangular

FUSIBLE LINK (replaceable)
Standard 165 ° F
(212 F MAXIMUM)

ROLL FORMED AND GALVANIZED ALL STEEL FRAME 22 GAUGE MINIMUM

4-1/4"

5/8"

TOP OF INSTALLED DAMPER

U.L. APPROVED FLEXIBLE FIRE BLANKET (SHOWN IN THE CLOSED POSITION)

STEEL RIVETED AND METAL FORMED ASSEMBLY

(2) NEGATOR STAINLESS STEEL CLOSURE SPRINGS MOUNTED ON SPRING PIN BRACKETS

STEEL BLADE 22 GA. & INSULATION BLANKET

HORIZONTAL MOUNTING

Model 45
U.L. Classified
3 Hour Rating

type
45-LT

LOOK FOR THESE LABELS

UNDERWRITERS LABORATORIES (UL555C)
 CLASSIFIED CEILING RADIATION DAMPERS.
 FIRE RESISTANCE RATED 3 HOUR.
 FOR USE IN UL CLASSIFIED BUILDING
 MATERIALS RATED 3 HOUR OR LESS.

ORDER WIDTH LESS 1/4"

ORDER HEIGHT LESS 1/4"

Model 45-LT

Standard material construction galvanized steel.

SINGLE SECTION SIZE AVAILABILITY		
HORIZONTAL		
	WIDTH	HEIGHT
MINIMUM	4"	4"
MAXIMUM	14'	14"

JOB NAME: _____


LOCATION: _____

ARCHITECT: _____

ENGINEER: _____

CONTRACTOR: _____

10253-REV-C-1



LLOYD INDUSTRIES INC.

231 COMMERCE DRIVE
MONTGOMERYVILLE, PA. 18936
TEL: 215-412-4445
FAX: 215-412-4409
EMAIL: LLOYDIND@FIREDAMPER.COM

5858 BROADWAY AVE.
JACKSONVILLE, FL. 32254
TEL: 904-378-8440
FAX: 904-378-8441
EMAIL: LLOYDINDI@BELLSOUTH.NET

WEB SITE: FIREDAMPER.COM