Wireless TAP Set

TAP

Wireless Temperature and Pressure Gauge Set

The new wireless digital pressure and temperature gauge set TAP is a user friendly measuring instrument to measure temperature and pressure from the low and high sides of air conditioning and refrigeration systems.

- Quick and easy connection to pressure source and temperature measuring point.
- The wireless K-type temperature clamp, equipped with digital display, is applicable for pipe diameters from 1/4" to 1 5/8".
- Measurements and calculation of superheat or subcooling can be shown on pressure gauge display and / or on your mobile device.
- Up to 6 TAP devices can be monitored on your mobile device.
- Create report on mobile phone and send by e-mail to your office.
- Use of common AAA batteries.
- TAP is delivered in a handy case either as single or double set.

Features and Benefits

Display on pressure gauge



Display on temperature clamp



Wireless no cable needed



No smart device needed



IOS compatible



Android compatible



Synchronized with App



Calculate superheat and subcooling



Reports stored on smart device and E-mailed



Library of over 50 refrigerants stored



Connect up to 6 pressure gauges and temperature clamps



Pressure Gauge and Temperature Clamp stand alone




Refrigerant updates available via Micro USB connection



Online - Offline





Technical Specification

TAP Pressure Gauge

Refrigerant:	More than 50 refrigerant tables included
Pressure range:	Up to 870 psi
Accuracy:	≤ 1.0 % FS
Resolution:	0.1 psi
Units:	psi / bar / kPa / MPa
Backlit LCD display:	1-9/16" x 1-3/16"
Automatic power save mode:	Configurable: 10 min / 20 min / Off
Low battery indication:	When battery level is less 30%
Power:	Battery 4 x AAA
Battery life:	40 h
Interface:	Micro USB
Connection fitting:	1/4" SAE
Including adapters:	1/4" SAE female/female
Size:	5" x 2-1/4" x 1-11/32"
Weight:	7 oz

TAP Temperature Clamp

Type:	K-Type
Temperature range:	-40°F to +257°F
Accuracy:	± 1.8°F
Resolution:	0.2°F
Temperature units:	°F/°C
Backlit LCD display:	1-3/8" x 19/32"
Power:	Battery 3 x AAA
Battery life:	50 h
Jaw range:	1/4" to 1 5/8"
Size:	6-3/8" x 1-9/16" x 3-9/64"
Weight:	6 oz

App Requirements

iOS:	Version 8.0 or higher
Android:	Version 4.4 or higher
Get the App for iPhone, iF for Android on Play Store	^p ad on App Store™,

Designation	Description	Part No.
TAP-SET	 1 TAP Pressure Gauge 1 TAP Temperature Clamp 1 SAE ¼" female/female adapter 1 USB Cable 7 Batteries 1 Manual 1 Case 	4687788
TAP-DOUBLE-SET	 2 TAP Pressure Gauges 2 TAP Temperature Clamps 2 SAE ¼" female/female adapter 1 USB Cable 14 Batteries 1 Manual 1 Case 	4687789
TAP	Pressure Gauge	4687787
TAP-CLAMP	Temperature Clamp	4687785

Further available accessories (optional)				
SWIVEL-ARM- 1/4"SAE-N	Swivel arm 1/4" SAE	4687631		
QC-S410A/2	Adapter with core depressor, 1/4" SAE x 5/16"SAE, 2 pcs	4687095		
QC-S4A- 1/4"SAE/2	Quick coupler straight 1/4" SAE x 1/4" SAE, 2 pcs.	4687823		
QC-S4A- 5/16"SAE/2	Quick coupler straight 1/4" SAE x 5/16" SAE, 2 pcs.	4687824		
TAP-MARKING- RING-SET	Marking rings for TAP 4x5 pcs. per size	4687793		
TAP-SET-CASE	Case for TAP-SET	4687860		
TAP-DOUBLE- SET-CASE	Case for TAP-DOUBLE-SET	4687859		