



Residential General "G" Filters

1A-10G

Specifications

Machined Aluminum Head with 1/8" Vacuum/Bleed port with #G epoxy-Coated Disposable Spin-On Cartridge Filter.

Maximum Firing Rate: 10 gph
 Micron Removal: 10 microns
 Filtering Area: 500 sq in
 Working Pressure: 15 psi
 Flow Rate: 45 gph
 Inlet / Outlet: 3/8" npt
 Dimensions: 7-1/8" H x 3-3/4" W



1005

1A-10G General Turrent-On Spin-On Fuel Oil Filter

1A-10GBK

Specifications

Machined Aluminum Head with 1/8" Vacuum/Bleed port with #G epoxy-Coated Disposable Spin-On Cartridge Filter.

Maximum Firing Rate: 10 gph
 Micron Removal: 10 microns
 Filtering Area: 500 sq in
 Working Pressure: 15 psi
 Flow Rate: 45 gph
 Inlet / Outlet: 3/8" npt
 Dimensions: 9" H x 4-3/4" W



1006

1A-10GBK General Turrent-On Spin-On Fuel Oil Filter

G

Specifications

Machined Aluminum Head with 1/8" Vacuum/Bleed port with #G epoxy-Coated Disposable Spin-On Cartridge Filter.



2008

"G" Epoxy-Coated Can Repl Cartridge

Spin-On Accessories



3620

AMB (B) Angle Filter Mounting Bracket



3610

FRI (K) 30" Vacuum Filter Restriction Indicator (Gauge)



3600

11V (1A) Alum Residential Filter Head w/Port