

GAR-BER SPIN-ON FUEL OIL FILTERS

Residential Gar-Ber "R2000" Filters

11V-R2000

Specifications

Machined Aluminum Head, with
1/8" Vacuum/Bleed port with
#R-2000 Epoxy-Coated
Disposable Spin-On Filter.

Maximum Firing Rate: 10 gph
Micron Removal: 10 microns
Filtering Area: 500 sq in
Working Pressure: 15 psi
Flow Rate: 45 gph
Inlet / Outlet: 3/8" npt
Dimensions: H-7½" W-3¾"

Standard With **BIOGasket™**



1608

11V-R2000 Gar-Ber Fuel/Oil
Filter with Water Block

11BV-R2000K

Specifications

Machined Aluminum Head,
Galvanized Attaching Bracket,
Filter Restriction Indicator,
and #R-2000 Epoxy-Coated
Disposable Spin-On Filter.

Inlet/Outlet: 3/8" npt
Dimensions:
Bracket Up Position: H-9¼"
Bracket Down Position: H-9" W-3¾"

Standard With **BIOGasket™**



1611

11BV-R2000K Gar-Ber Fuel/Oil
Filter with Water Block

R-2000

Specifications

Epoxy coated canister.
Recommended on units with
either single or double line
systems firing up to 10 gph.

Maximum Firing Rate: 10 gph
Micron Removal: 10
Filtering Area: 500 sq. in.
Working Pressure: 15 psi
Flow Rate: 45 gph
Dimensions: H-5½" W-3¾"

Standard With **BIOGasket™**



2630

"R2000" Epoxy-Coated ReplCar-
tridge with Water Block

Residential Gar-Ber "R" Filters

11V-R

Specifications

Machined Aluminum Head with
1/8" Vacuum/Bleed port with
#R epoxy-Coated Disposable
Spin-On Filter.

Maximum Firing Rate: 10 gph
Micron Removal: 10
Filtering Area: 500 sq. in.
Working Pressure: 15 psi
Flow Rate: 45 gph
Inlet/Outlet: 3/8" npt
Dimensions: H-7½" W-3¾"



1600

11V-R Gar-Ber Spin-On Fuel Filter

11BV-R

Specifications

Machined Aluminum Head, 1/8"
Vacuum/Bleed Port, #R Epoxy-
Coated Disposable Spin-On
Filter and Galvanized Attaching
Bracket.

Maximum Firing Rate: 10 gph
Micron Removal: 10
Filtering Area: 500 sq. in.
Working Pressure: 15 psi
Flow Rate: 45 gph
Inlet/Outlet: 3/8" npt
Dimensions:
Bracket Up Position: H-9¼"
Bracket Down Position: H-7½" W-3¾"



1602

11BV-R Gar-Ber Spin-On Fuel Filter