

DYNAMIC FIRE DAMPERS

4-1/4"

Top Blade Riveted To Frame

Blade Section Cover Plate

1"

"B" PAN HEIGHT

OVERALL DAMPER HEIGHT

ORDER HEIGHT

Typical (3) Sides

Model 75LBV

3/4"

Interlocking Steel Blades 22 ga. min.

FUSIBLE LINK (replaceable) Standard 165 ° F (others available)

ROLLFORMED STEEL FRAME 22 ga. min.

Vertical Model 75 U.L. Classified 3 Hour Rating

type **LB-DY**

(DAMPER SUPPLIED)

"B" PAN

ORDER HEIGHT 1/4" LESS THAN ORDER HEIGHT

OVERALL HEIGHT

ORDER WIDTH (DAMPER SUPPLIED 1/4" LESS THAN ORDER WIDTH)

(V) VERTICAL MOUNT

LOOK FOR THESE LABELS

CLASSIFIED

UL

UNDERWRITERS LABORATORIES (UL555) CLASSIFIED FIRE DAMPERS. FIRE RESISTENCE RATED 3 HOURS. FOR USE IN UL CLASSIFIED BUILDING MATERIALS RATED 4 HOURS OR LESS.

Damper Model with Blades "Out of Air Sream".
Material Standard construction galvanized steel.
Dampers supplied 1/4" less than Order Width and Height.

	SINGLE SECTION SIZE AVAILABILITY			
	VERTICAL		HORIZONTAL	
	WIDTH X HEIGHT		WIDTH X HEIGHT	
MINIMUM	4"	3"	NOT AVAILABLE	NOT AVAILABLE
MAXIMUM SECTION	24"	24"	NOT AVAILABLE	NOT AVAILABLE
MAXIMUM DUCT SIZE			NOT AVAILABLE	NOT AVAILABLE

JOB NAME: _____

LOCATION: _____

ARCHITECT: _____

ENGINEER: _____

CONTRACTOR: _____

CLLOYD-13-REV-C-1



LLOYD INDUSTRIES INC.

231 COMMERCE DRIVE
MONTGOMERYVILLE, PA. 18936
TEL: 215-412-4445
FAX: 215-412-4409
EMAIL: LLOYDIND@FIREDAMPER.COM

5858 BROADWAY AVE.
JACKSONVILLE, FL. 32254
TEL: 904-378-8440
FAX: 904-378-8441
EMAIL: LLOYDINDI@BELLSOUTH.NET

WEB SITE: FIREDAMPER.COM