Required information:

ne	quired information.		
1.	What is the depth of the louver?		
2.	What are the dimensions of the louver? width" x height" x		
	se note: Dampers are supplied 1/4" less than order width and height (by inches) unless the ual size" is specified.		
3.	 What is the frame type of the louver? Channel frame: provide consistent outside dimensions around a louver's perimeter and can be installed flush with the face of a wall (inset from a face) or slid inside a sleeve. Flanged: helps hide inconsistent gaps between louvers and the opening caused by uneven sizes or out of square conditions. 		Model 2SRF
4.	What type of louver do you need?		
	Storm Resistant (Available in 2" and 4" deep models)		
	Drainable (Available in 4" and 6" deep models)		
5.	What type of screen is required?		
٥.	Bird Screen (standard if not specified) - 1/2" x 1/2" mesh		
	Insect Screen - 1/16" x 1/16" mesh		Model 2SRCI
6.	What finish is desired?		model Editor
0.	Mill finish (standard if not specified)		
	Clear anodized		
	Anodized colors, consult factory for colors available		
	Baked enamel *	3	
	"Kynar" *		
lf	these items are selected, please indicate color choice here: no color has been specified, we will quote a standard color. At time of order, if		

















Lloyd Industries, Inc.

231 Commerce Dr. • Montgomeryville, PA 18936 Phone: 215-412-4445 • Fax 215-412-4409

www.firedamper.com

5858 Broadway Ave. • Jacksonville, FL 32254 Phone: 904-378-8440 • Fax 904-378-8441

