
CEILING RADIATION DAMPER WITH REGISTER BOX ASSEMBLY

MODEL CRD50-BT-6.0 MODEL CRD50-EA-BT-6.0

I HOUR RATED CRD/REGISTER/GRILLE ASSEMBLY CRD/PLENUM BOX ASSEMBLY FOR FLOOR/CEILING AND ROOF/CEILING WOOD TRUSS ASSEMBLIES

"RECTANGULAR"

UL DESIGN L-563, P-544



CEILING RADIATION DAMPER

- 1. UL LISTED LINK (165°F STANDARD)
- 2. BLADES 22 (.853mm) GA. GALV. STEEL
 3. CERAMIC FIBER WITH FIBERGLASS COVER*
 4. ROLL—FORMED FRAME 22 (.853 MM) GA. GALV. STEEL PLENUM BOX
- 1. OUTER BOX: 28 GAUGE GALVANIZED STEEL
- 2. COLLAR: ROLL FORMED 28 GALGE GALVANIZED STEEL WITH ROLL FORMED 1/4" BEADING.
- 3. INSULATION: FIBERGLASS DUCT BOARD 1-1/2" THICK (R-6.0)
- 4. "C" DIAMETER PROVIDED NOMINAL ORDER DIAMETER.

- NUIES:

 1. MAXIMUM REGISTER SIZE 16" X 16" X12" DIAMETER COLLAR.

 MINIMUM REGISTER SIZE 4 X 4" X 2" DIAMETER COLLAR.

 SEE THE CATALOG FOR FULL LISTING OF AVAILABLE STOCK SIZES.
 FOR NON-STANDARD SIZES CONSULT THE FACTORY.

 2. AVAILABLE IN STAINLESS STEEL
- 3. AVAILABLE WITH EXTENDED LENGTH DRYWALL FLANGE
- 4. MANUFACTURED WITH BLADES OPENING AS SHOWN: EXCEPT WHEN REGISTER WIDTH "W" IS LESS THAN 6".
- 5. MINIMUM CRD50-EA-BT-6.0 REGISTER SIZES NOT LESS THAN 6" ON WIDTH AND 6" ON HEIGHT.
- 6. REGISTER/GRILLE (STEEL) SUPPLIED BY OTHER.
- * 7. CERAMIC INSULATION IS NOT REQUIRED ON DAMPERS WITH AREAS LESS THAN 80 SQUARE INCHES AND IS OPTIONAL DAMPERS ABOVE 80 SQUARE INCHES WILL BE PROVIDED WITH BLADE INSULATION.
- 8 MEETS UL263, NFPA 90A REQUIREMENTS



APPLIED RESEARCH LABORATORIES (UL555C) CLASSIFIED CEILING RADIATION DAMPERS. FIRE RESISTENCE RATED 1 HOUR. FOR USE IN UL CLASSIFIED BUILDING MATERIALS RATED 1 HOUR OR LESS.

"B"
CC- DIA
REGISTER WIDTH REGISTER
Model CRD 50-EA-BT SHOWN

ORDERING: CRD 50-EA-BT-6.0-10"W X 6"H X 5" DIA.

JOB NAME:	
LOCATION:	
ARCHITECT:	
ENGINEER:	
CONTRACTO	₹:

10213-REV-G-ARL



INDUSTRIES

231 COMMERCE DRIVE MONTGOMERYVILLE, PA. 18936

TEL: 215-412-4445 FAX: 215-412-4409

EMAIL: LLOYDIND@FIREDAMPER.COM

5858 BROADWAY AVE. JACKSONVILLE, FL. 32254

TEL: 904-378-8440 FAX: 904-378-8441

EMAIL: LLOYDINDI@BELLSOUTH.NET

WEB SITE: FIREDAMPER.COM