



ST101 - ST104

General Purpose Timer Switches

Supco's 24 hour time controls offer economical electro-mechanical switching of electrical loads for single and double pole applications.

Features:

- Dial: 24 Hour, 2 ON and 2 OFF trippers.
- Switch Rating: 40 amps resistive or tungsten, 1000 VA pilot duty, 2 hp at 120 volts and 5 hp at 240 volts.
- Operations: Up to 10 ON/OFF operations per 24 hours. With manual ON/OFF switch that allows circuit to be hand operated without disturbing the scheduled setting.
- Minimum Setting: 1 hour between ON/OFF, 2 hours between OFF/ON.
- Enclosure: Non corrosive NEMA 1.
- For additional tripper pairs, order part number STPIN.

Applications:

- Off-cycle defrost
- Pool filter pumps and heaters
- Indoor and outdoor lighting
- Sprinkler systems
- Greenhouse lighting and ventilation



Specifications:

PART NO.	VOLTS	SWITCH	CROSS REFERENCE
ST101	120	SPST	Paragon® 4001-00, Intermatic® T101, Precision® CD101
ST102	240	SPST	Paragon® 4002-71, Intermatic® T102, Precision® CD102
ST103	120	DPST	Paragon® 4003-00, Intermatic® T103, Precision® CD103
ST104	240	DPST	Paragon® 4004-71, Intermatic® T104, Precision® CD104



- Steel Case Dimensions: 7.9" X 5.3" X 3" (20cm X 13.5cm X 7.7cm)
- Unit Weight: 2.87 lbs. (1300 grams)
- Temperature Range: -22°F to 158°F (-30°C to 70°C)

F433 - 05242010

SEALED UNIT PARTS CO., INC
 PO Box 21, 2230 Landmark Place, Allenwood, NJ 08720 USA
 Phone: 732-223-6644 Fax: 732-223-1617
 www.supco.com • info@supco.com