

Capacitors



Motor Start Capacitors

UL approved Start Capacitors available in 110 VAC, 165 VAC, 220 VAC and 330 VAC.



Features

- Dry, electrolytic, no polarized type for intermittent duty in AC motors and compressors.
- Used where starting torques must be higher in relation to running torques.
- Moisture and oil resistant molded phenolic resin or plastic material.
- Standard dual blade terminals.
- Industry standard case sizes.

compressors.

110 VAC

PART NO.	VALUE (µF)	CASE SIZE
CS21-25X110	21-25	1
CS25-30X110	25-30	1
CS30-36X110	30-36	1
CS36-43X110	36-43	1
CS43-56X110	43-56	1
CS56-72X110	56-72	1
CS64-77X110	64-77	1
CS72-88X110	72-88	1
CS88-108X110	88-108	1
CS108-130X110	108-130	1
CS124-156X110	124-156	1
CS145-175X110	145-175	1
CS161-193X110	161-193	1
CS189-227X110	189-227	1
CS200-240X110	200-240	2
CS216-259X110	216-259	2
CS233-292X110	233-292	4
CS270-324X110	270-324	4
CS300-360X110	300-360	4
CS324-388X110	324-388	4
CS340-408X110	340-408	4
CS378-440X110	378-440	4
CS400-480X110	400-480	5
CS460-552X110	460-552	5
CS540-648X110	540-648	5
CS590-708X110	590-708	5
CS708-850X110	708-850	7
CS829-995X110	829-995	8
CS1000-1200X110	1000-1200	8

165 VAC

PART NO.	VALUE (µF)	CASE SIZE
CS124-156X165	124-156	4
CS145-175X165	145-175	4
CS161-193X165	161-193	4
CS233-292X165	233-292	5
CS270-324X165	270-324	5

220 VAC

PART NO.	VALUE (µF)	CASE SIZE
CS21-25X220	21-25	1
CS25-30X220	25-30	1
CS30-36X220	30-36	1
CS36-43X220	36-43	1
CS43-56X220	43-56	2
CS56-72X220	56-72	2
CS64-77X220	64-77	4
CS72-88X220	72-88	4
CS88-108X220	88-108	4
CS108-130X220	108-130	4
CS124-156X220	124-156	5
CS145-175X220	145-175	7
CS161-193X220	161-193	7
CS189-227X220	189-227	7
CS216-259X220	216-259	8
CS233-292X220	233-292	8
CS270-324X220	270-324	8

330 VAC

PART NO.	VALUE (µF)	CASE SIZE
CS21-25X330	21-25	1
CS25-30X330	25-30	1
CS30-36X330	30-36	4
CS36-43X330	36-43	4
CS43-56X330	43-56	4
CS53-70X330	53-70	5
CS56-72X330	56-72	5
CS72-88X330	72-88	5
CS88-108X330	88-108	7
CS108-130X330	108-130	8
CS124-156X330	124-156	8
CS130-156X330	130-156	8
CS145-175X330	145-175	8
CS161-193X330	161-193	8
CS189-227X330	189-227	8
CS216-259X330	216-259	8
CS270-324X330	270-324	8
CS324-388X330	324-388	8

Case Dimensions

CASE SIZE	DIAMETER	HEIGHT
1	1 7/16"	2 3/4"
2	1 7/16"	3 3/8"
4	1 13/16"	3 3/8"
5	1 13/16"	4 3/8"
6	2 1/16"	3 3/8"
7	2 1/16"	4 3/8"
8	2 9/16"	4 3/8"

Wiring Diagrams for Run Capacitors

