Service & Installation Products

LI'L Popper Control Board Circuit Breaker

The POP3 or POP5 provide a temporary emergency fix for control boards that continue to blow fuses or that are shorted out.



Features/Benefits

- Two common sizes to choose from: 3 or 5 amp
- · Includes quick setting thermal cut out.
- · Self-adhesive backing for easy temporary installation
- Keeps homeowner and or building owner up and running with no inconvenient down time until the original control board can be replaced.

Applications

- Gas Fired Egiupment
- Furnaces
- Roof Top Units
- Boilers
- Unit Heaters
- Water Heaters
- Pool Heaters
- Fireplaces

Hot Tubs

Product Information

PART NO.	Voltage	DESCRIPTION
POP3	24	3 amp control board circuit breaker
POP5	120/240	5 amp control board circuit breaker

Tech Tip

· SUPCO recommends using the Li'L Popper as a "temporary fix" only, until the original control board can be replaced.

ECAP321 High Efficiency PVC Flue Cap

The affordable approach to flue pipe problems starts at the TOP! The ECAP321 PVC Flue Cap protects today's high efficiency furnaces from dirt, moisture and other debris.





Features/Benefits

- Protection for high efficiency furnaces
- Universal flue cap fits 1.5", 2" and 3" PVC pipe
- · Reduces draft inducer motor rust
- · Helps to eliminate pressure switch service calls
- · Resistant to UV radiation and oxidative degradation
- CSA approved for use in 90% AFUE heating applications

Applications

- 90% high efficiency furnaces with a PVC flue pipe
- · Used for vertical or horizontal venting applications





Anti-Vibration Pads

SUPCO offers four different types of Anti Vibration Pads that provide vibration dampening and leveling of HVAC/R, Appliance and Industrial equipment.

General Description

DESCRIPTION

PART

SIS018

NO.



All Rubber

Rubber & Cork

- Three different types include Rubber & Cork, All Rubber and ISO Cube.
- · Made of the highest quality elastomeric materials.
- Oil, chemical & age resistant padding.
- · Maximum load capacity
 - 50 psi for Rubber & Cork and All Rubber.
 - 180 psi for the ISO Cube.

CARTON

QTY.

Applications

- Air Conditioners
- Heat Pumps
- Furnaces
- Boilers
- Air Handlers
- Compressors
- Ice Machines
- Refrigerators
- Washers

- Dishwashers
- Stoves & Ovens
- Presses
- Machinery

Dryers

- Shelving

Specifications

- · Pull Strength: 6.5 Mpa
- Extension Rate Until Broken: 310%
- Permanent Distoration Rate Until Broken: 12%



SP2C	2" x 2" x 7/8" Rubber/Cork Pad	48
SP3C	3" x 3" x 7/8" Rubber/Cork Pad	36
SP4C	4" x 4" x 7/8" Rubber/Cork Pad	24
SP6C	6" x 6" x 7/8" Rubber/Cork Pad	24
SP12C	12" x 12" x 7/8" Rubber/Cork Pad	12
SP18C	18" x 18" x 7/8" Rubber/Cork Pad	6
	ALL RUBBER ANTI VIBRATION PADad	
SP2	2" x 2" x 3/8" All Rubber Pad	48
SP3	3" x 3" x 3/8" All Rubber Pad	36
SP4	4" x 4" x 3/8" All Rubber Pad	24
SP6	6" x 6" x 3/8" All Rubber Pad	24
SP18	18" x 18" x 3/8" All Rubber Pad	6
	ISO CURE ANTI VIRRATION DAD	

18" x 18" x 3/4" ISO Cube

RUBBER & CORK ANTI VIBRATION PAD