

Condensate Drain Pans



Commercial Condensate Evaporator Pans

For condensate applications where no drain is available, choose from these popular, large capacity sized pans. SUPCO commercial refrigeration condensate evaporator pans are made from top quality materials for durable, long life.

Features/Benefits:

- CP804-HD 20 guage stainless steel. All others use 22 guage.
- Corrosion resistant stainless steel construction.
- Made from top quality materials and components for longer more durable use.
- Positive evaporation
- High limit safety and float switch operation
- Available In 120 volts, 208 volts and 240 volts
- Warranty-One Year from date of installation
- Space saving

Applications:

- Evaporates defrost and condensation where no drain is available.
- Used in supermarket refrigeration systems and elevators.
- These pans are used for water dissipation **ONLY! DO NOT OPERATE "DRY"**.
- Clean the pan and check the float every 30 days for optimum performance and operation.



Specifications

PART NO.	CAPACITY	VOLTS	WATTS	AMPS	DIMENSIONS L x W x H	DISSIPATION RATE	
						PER DAY	REPLACES
CP801	1 3/4 qt	120	400	3.3	10" x 7" x 2 1/2"	3 Gallon	DM04T1S
CP802	2 1/2 qt	120	800	6.6	13" x 7" x 2 1/2"	6 Gallon	DM08S1S
CP802-240	2 1/2 qt	240	800	3.3	13" x 7" x 2 1/2"	6 Gallon	
CP804	4 1/2 qt	120	1000	8.34	13" x 7" x 4"	10 Gallon	DM10MS1
CP804-240	4 1/2 qt	240	1000	4.17	13" x 7" x 4"	6 Gallon	
CP804HD	7 1/2 qt	120	1000	8.34	13" x 10" x 4"	6 Gallon	DM10W1D
CP804HD-240	7 1/2 qt	240	1000	4.17	13" x 10" x 4"	6 Gallon	
CP807	7 1/2 qt	120	1000	8.34	13" x 10" x 4"	10 Gallon	DM10W1S
CP807-240	7 1/2 qt	240	1000	4.8	13" x 10" x 4"	10 Gallon	DM10W3
CP815	15 qt	120	1440	12	21" x 13" x 4"	12 Gallon	DM15WW1D
CP815-240	15 qt	240	1500	6.28	21" x 13" x 4"	12 Gallon	DM15WW3
CP816	7 qt	120	500	4.17	13" x 10" x 4"	4.5 Gallon	DM05W1D
CP817	7 qt	208	1000	4.81	13" x 10" x 4"	8 Gallon	DM10W2D
CP818	7 qt	208	1000	4.81	13" x 10" x 4"	8 Gallon	DM10W2S
CP819	7 qt	120	1500	12.5	13" x 10" x 4"	12 Gallon	DM15W1D
CP820	7 qt	208	1500	7.21	13" x 10" x 4"	12 Gallon	DM15W2D
CP821	7 qt	208	1500	7.21	21" x 10" x 4"	12 Gallon	DM15WW2D

Replacement Parts

PART NO.	FLOAT PART NO.	HEATER PART NO.	MICROSWITCH PART NO.	THERMOSTAT PART NO.
CP801	CPFLOAT	CPH801	CPS800	CPT800
CP802	CPFLOAT	CPH802	CPS800	CPT800
CP802-240	CPFLOAT	CPH802-240	CPS800	CPT800
CP804	CPFLOAT4	CPH8047	CPS800	CPT800
CP804-240	CPFLOAT4	CPH804-240	CPS800	CPT800
CP804HD	CPFLOAT4	CPH804HD	CPS800	CPT800
CP804HD-240	CPFLOAT4	CPH804HD-240	CPS800	CPT800
CP807	CPFLOAT4	CPH8047	CPS800	CPT800
CP807-240	CPFLOAT4	CPH807-240	CPS800	CPT800
CP815	CPFLOAT4	CPH815	CPS800	CPT800
CP815-240	CPFLOAT4	CPH815-240	CPS800	CPT800
CP816	CPFLOAT	CPH816	CPS800	CPT800
CP817	CPFLOAT	CPH817	CPS800	CPT800
CP818	CPFLOAT	CPH818	CPS800	CPT800
CP819	CPFLOAT	CPH819	CPS800	CPT800
CP820	CPFLOAT	CPH820	CPS800	CPT800
CP821	CPFLOAT	CPH821	CPS800	CPT800

Cross Reference on page 129

70 Condensate Drain

Authorized, cost effective replacement drain for most commercial refrigerators and freezers.

Features/Benefits:

- PTC Control supplies only required heat to evaporate water.
- Thermostat and float NOT required
- Self regulating
- Uniform heating
- Die cast aluminum eliminates corrosion
- Removable cord set for easy cleaning
- Die cast aluminum eliminates corrosion
- Removable cord set for easy cleaning
- Die cast aluminum eliminates corrosion
- Removable cord set for easy cleaning
- Fast evaporation rate (6 oz./ hour)
- Low Profile(3") to fit tight spaces
- NSF, UL and CSA(where noted) approved



PART NO.	CAPACITY	VOLTS	WATTS	AMPS	EVAPORATE.	
					RATE	SIZE
70	50 oz	115	300	2.61	6 oz/hr	12 1/4" x 4 3/4" x 3"
70-220	50 oz	220	300	1.36	6 oz/hr	12 1/4" x 4 3/4" x 3"
70CSA*	50 oz	115	190	1.65	6 oz/hr	12 1/4" x 4 3/4" x 3"
70CSA220*	50 oz	220	190	.86	6 oz/hr	12 1/4" x 4 3/4" x 3"

*CSA indicates CSA approval. ** All are 50/60 HZ

30-OS, 31 & 75 Condensate Drains

- Standard cast aluminum condensate drains complete with long life heating element and mounting legs.
- Designed for continuous use.



PART NO.	CAPACITY	VOLTS	WATTS	AMPS	EVAPORATE.	
					RATE	SIZE
30-OS*	38 oz	120	160	1.33	8 oz/hr	10" x 4" x 2 7/8"
30-220-OS*	38 oz	220	160	.73	8 oz/hr	10" x 4" x 2 7/8"
31	50 oz	120	160	1.33	6 oz/hr	10" x 4 1/2" x 3 3/8"
31-220	50 oz	220	160	.73	6 oz/hr	10" x 4 1/2" x 3 3/8"
75	75 oz	120	320	2.67	14 oz/hr	10" x 9" x 2 3/4"
75-220	75 oz	220	320	1.45	14 oz/hr	10" x 9" x 2 3/4"

* Indicates NSF listing ** All are 50/60 HZ

Wall Mount Brackets

PART NO.	CONDENSATE DRAIN NO.
30WM	30-OS Series, 75 Series
31WM	31 Series