



LLS LOGiT PC Software and Interface for Serial Connection

- PC Software on CD ROM
- LINT Interface
- Cable for LOGiTs to Serial Port (CABLE6)



LLSU LOGiT PC Software and Interface for USB Connection

- PC Software on CD ROM
- LINTU Interface
- Cable for LOGiTs to USB Port (19449)

Benefits/Specifications

- Compatible with Windows 95 and above
- Graphic and Text Data
- 3 Memory modes: Stop on full, record continuously, or memory rollover
- Real time monitoring
- Password protected calibration of each channel
- Data exportable to Text or Excel
- Maximum Serial Interface 50 feet.
- Minimum System Requirements: 8MB RAM, 2MB Disk Space, 800 x 600 Resolution, COM port or USB port

LOGiT Accessories

Standard Accessories		LT2	LTH	LTC	LTT	LPT	LCV	L420
14265-001	15' Remote Temperature Sensor	*				*		
DLTP6	4" Stainless Steel 6' Temperature Sensor				(2)			
TPFDA	K-type Thermocouple with 4' FDA Approved Insulation			*				
12867	300 A Current Probe†						*	

Optional Accessories		LT2	LTH	LTC	LTT	LPT	LCV	L420
LITH9B	Lithium Battery	*	*		*	*	*	*
USBS	USB to Serial Interface	*	*		*	*	*	*
LLS	LOGiT PC Software & Interface	*	*	*	*	*	*	*
LLSU	LOGiT PC Software & Interface	*	*	*	*	*	*	*
SW25	25' Temperature Sensor Extension Wire	*				*		
SW50	50' Temperature Sensor Extension Wire	*				*		
SW75	75' Temperature Sensor Extension Wire	*				*		
SW100	100' Temperature Sensor Extension Wire	*				*		
CABLE10T	10' Sensor Extension Wire					*		
CABLE10H	10' Sensor Extension Wire (Max 3)				*			

†Pressure probe must be factory calibrated with LPT logger

*Current sensor must be factory calibrated with LCV logger