



12 per case

M44 Aerosol Lubricant & Metal Protectant

Specially created and perfected for Professional technicians and mechanics everywhere... and there is nothing like it in the world!

- Turns old tools into new ones
- Can be used on cars, trucks, bicycles, fishing gear, marine gear, electrical and electronic gear, machinery, appliances etc.

Applications

- Lubricates
- Prevents Rust and Corrosion
- Repels Moisture
- Restores Tools and Equipment



M098



M044

M098 Zoom Spout® Oiler

A paraffin base, non-gumming, high quality lubricating oil

- All-Purpose Lubricating Oil
- Flexible spout extends and retracts, adjusts to any "in-between" length
- Withstands high temperatures without breaking down
- Viscosity 92-99 @ 140°F

Applications

- All types of motors, blowers, oil burner bearings, linkages, appliance pumps, etc...
- Normal and High speed shaft bearings

Rust Buster® Solvent

Dissolves Rust

- Telescoping Pullout Spout
- Loosens rust in seconds
- No lingering odor
- Counter Display Case

| PART NO. | BOTTLE SIZE | PACKAGING |
|----------|-------------|-----------|
| M098 | 4 oz | 12/Case |
| M044 | 4 oz | 12/Case |

SUPCO88 Oil Additive

Introduced in 1954 and valued worldwide, this super lubricant is a "must use" in repair and preventative maintenance programs.

- Compatible with all refrigeration oils
- Dissolves sludge buildup on bearing and valve surfaces
- Prevents binding of high speed compressors
- Prevents excess wear in motors and compressors

| PART NO. | BOTTLE SIZE | PACKAGING |
|----------|-------------|-----------|
| S8 8 OZ. | 24/Case | |

Application Notes:

To Prevent Excess Wear on Expansion Valves and Capillaries Mix one part SUPCO88 to 9 parts refrigeration oil.

- Prevents excess wear on expansion valve needles and seats.
- Penetrates the pores of ALL moving metal parts of the expansion valve for constant lubrication.

Extend the Life of ALL Motors (i.e. for Blowers and Air Conditioners)

- A few drops will help free a "frozen" or sticking motor shaft
- Mix 9 to one for regular bearing maintenance.
- Decreases "bearing to shaft" friction and sludge accumulation when mixed 9 to one.

More Efficiency for High Speed Compressors

- Increases the lubricating capability of mineral oils in high speed compressors.
- Used in new units to reduce current draw by reducing friction and preventing overloading.
- SUPCO88 can be left in the system permanently.



S0100/ST200

Slimeout®

Condensate Pan Conditioning Tablets

- Slimeout® tablets prevent plugging of the air conditioning condensate drip pans and drain lines
- Slimeout® does not release any chlorine or other noxious fumes
- Slimeout® eliminates odors
- Slimeout® easily solves problems

| | PART NO. | PART NO. |
|---------------------|---------------|---------------|
| | S0100 | ST200 |
| Description | Slime Out | Slime Tab |
| Tablets Jar | 100 | 200 |
| Tablet Size | 35 grams | 20 grams |
| Initial Application | 2 tabs/3 tons | 3 tabs/3 tons |
| Maintenance | 2 per month | 3 per month |