

Chemicals



Leak Lock and Leak Lock GOLD with Teflon

A resin based soft setting brushable paste pipe joint compound resistant to all refrigerants, oils, water and most chemicals, liquids and gases.



- Use with pressures to 10,000 PSI to full vacuums.
- Temperature range -200°F to 400°F, (-93°C) to (204°C).
- It never hardens and it never becomes brittle.
- Ideal for joining all metals, plastics and other materials.
- Will stick to all clean surfaces.
- GUARANTEES A PERFECT SEAL... UNDER ALL CONDITIONS
- Will stick to all clean surfaces.
- Prevent vibration from loosening nuts, bolts, plugs and fittings.
- Non Toxic

Regular

PART NO.	SIZE	PKG
HS10001	1 1/3 oz Tube	12/Case
HS10004	4 oz Brush Top Plastic Jar	12/Case
HS10016	16 oz Brush Top Plastic Jar	12/Case
HS10128	1 Gallon Can	1

Teflon

PART NO.	SIZE	PKG
HS11001	1 1/3 oz TUBE	12/Case
HS11004	4 oz Brush Top Plastic Jar	12/Case
HS11016	16 oz Brush Top Plastic Jar	12/Case
HS11128	1 Gallon Can	1

Red Epoxy

When you need a sealant you can count on. High Performance, Heat Cured, Two Part, Epoxy Kit

- Exhibits a Color Change When Cured (Turns Gold)
- May Be Cured With a Hot Air Gun or Open Flame in Minutes
- -100°F to 300°F, (-73°C to 149°C)
- Working Pressure in Excess of 3000 PSI
- Tensile Strength: 6000 PSI
- Works on Vertical Surfaces
- Pressure Tested to 3000 PSI
- Simple, Quick Mixing & Application
- Oil, Gas, Fuel & Solvent Resistant
- No Rush, No Wait, You Control Curing Time
- Equipment is Serviceable Immediately
- Use on All Metals and Rigid Plastics
- HVAC & Refrigeration
- Plumbing & Appliances
- Automotive & Marine
- Petrochemical, Manufacturing
- Industrial, Commercial, Institutional



PART NO.	SIZE	PKG
HS12001	Kit Including 2 1/2 oz Tubes	12/Case

Solderlene

High Quality, Paste Type, Non-Acid Soldering Flux.

- Industrial strength wetting agents to promote solder flow
- For use with low and mid-temp. soft solders, both lead and lead-free
- Effective on all metals except aluminum and magnesium.
- Brush Top Plastic Jars



PART NO.	SIZE	PKG
HS30004	4 oz	12/Case
HS30016	16 oz	12/Case

Thawzone (New Formula)

The original liquid dehydrant, frees your frozen system in minutes. It seeks out moisture and chemically bonds to it.

- Enhanced moisture control in even the most advanced systems.
- Aids with oil return in low temperature systems.
- Compatible with all refrigerants and refrigeration lubricants.
- Helps prevent the formation of acid.
- No Methanol
- Environmentally Sound

- Safer
- Biodegradable, non-polluting
- Non-Poisonous

PART NO.	SIZE	PKG
HS17001	1 oz	24/Case
HS17004	4 oz	12/Case
HS17016	16 oz	6/Case

Add 1/8 fluid ounce (3.75 ml) of THAWZONE directly to the refrigerant of any system for every 1 lb. of refrigerant in the system.

*HIGHSIDE SYSTEM INJECTOR (part no. HSINJ001) IS RECOMMENDED FOR INTRODUCING THAWZONE INTO AN OPERATING SYSTEM.

Spiro Lite UV Bulb

120 Volt Florescent UV Light Source
For Your Light Trouble

PART NO.	PKG
HSUVB001	1

