



Enter Search Keyword

Product Category

HVAC Parts

Commercial Refrigeration

Test Instruments and Alarms

Tools and Chemicals

Air Conditioning Equipment

Appliance Parts

- Dishwasher Parts

- Dryer Parts

- Range Parts

- Refrigerator Parts

- Washer Parts

About Us    Distributors    Contact Us    Track Your Order    New Products

Zoom



Hover over picture to Zoom  
Click to enlarge

**COOL  
COOL-REFRIG & AC SURGE  
PROTECT**

Professional surge protectors for appliances. When present the PRO-TECTOR will either clamp the voltage to ground or absorb the energy of the surge.

**Features/Benefits**

- Short cycle protection
- Helps prevent blown fuses
- Prevents operation in low voltage conditions
- Prevents false starting attempts
- Easy installation
- LED to indicate proper operation
- Automatically restarts

Locate a Distributor Near You

Specifications    Applications    Downloads    Cross Reference    Accessories

Power consumption:	Maximum 10 Ma
Maximum protection level:	780 VAC (L-N), 1050 VAC (L-G,N-G)
Maximum energy dissipation:	448 joules
Operating temperature:	14°F to 158°F (-10°C to 70°C)
Maximum surge current amps:	24000
Time delay:	3-5 minutes
Maximum sw itching:	1.0 hp @ 115 VAC (12,000 BTU)
Operating voltage:	115 VAC single phase
Minimum starting voltage:	90 VAC single phase



Appliance Replacement Parts Distributors

2014 SUPPLEMENT



2014 Supplement



HVAC/R & Test Instrument Catalog



Surge Protectors Warranty Registration Site



AHR Expo Mexico  
September 23-25 2014  
Centro Banamex, Mexico  
D.F.

