



Enter Search Keyword

Product Category

HVAC Parts

Commercial Refrigeration

Test Instruments and Alarms

Tools and Chemicals

Air Conditioning Equipment

Appliance Parts

- Dishwasher Parts

- Dryer Parts

- Range Parts

- Refrigerator Parts

- Washer Parts

About Us

Distributors

Contact Us

Track Your Order

New Products



Hover over picture to Zoom
Click to enlarge

**CORD120
CORD120-
SURGE PR**

Professional
When presen
clamp the vo
energy of the s

Features/B

- Short cycle
- Helps prev
- Prevents o
- Prevents fa
- Easy instal
- LED to indi
- Automatic



Locate a Distributor Near You

- Specifications
- Applications
- Downloads
- Cross Reference
- Accessories

| | |
|-----------------------------|-----------------------------------|
| Power consumption: | Maximum 10 Ma |
| Maximum protection level: | 780 VAC (L-N), 1050 VAC (L-G,N-G) |
| Maximum energy dissipation: | 448 joules |
| Operating temperature: | 14°F to 158°F (-10°C to 70°C) |
| Maximum surge current amps: | 24000 |
| Time delay: | 3-5 minutes |
| Maximum sw itching: | 1.0 hp @ 115 VAC (12,000 BTU) |
| Operating voltage: | 115 VAC single phase |
| Minimum starting voltage: | 90 VAC single phase |

Appliance Replacement Parts Distributors

Appliance Replacement Parts Distributors

2014 SUPPLEMENT



2014 Supplement



HVAC/R & Test Instrument Catalog



Surge Protectors Warranty Registration Site



AHR Expo Mexico
September 23-25 2014
Centro Banamex, Mexico D.F.

