



Enter Search Keyword

Product Category

HVAC Parts

Commercial Refrigeration

Test Instruments and Alarms

Tools and Chemicals

Air Conditioning Equipment

Appliance Parts

- Dishwasher Parts
- Dryer Parts
- Range Parts
- Refrigerator Parts
- Washer Parts

About Us Distributors Contact Us Track Your Order New Products



Zoom
Hover over picture to Zoom
Click to enlarge

**D4120
D4120--LOW FLOW DUCT SMOKE
DETECTOR**

The D4120 4-wire photoelectric duct smoke detector features a pivoting housing that fits both square and rectangular footprints and mounts to round or rectangular ductwork. This unit senses smoke in the most challenging conditions. Plug-in sensor head off

Features/Benefits

- Backward compatible with existing accessories
- Field selectable configuration settings
- Two DPDT relay contacts
- High contrast terminal designations
- Built-in short circuit protection
- Increased wiring space
- Easy access Test/Reset button
- Square or rectangular mounting options
- Plug-in sensor
- 4-wire Photoelectric, integrated low-flow technology

Locate a Distributor Near You

Specifications Applications Downloads Cross Reference Accessories

Air Duct Velocity:	100 to 4000 ft/min
Operating Humidity:	0 to 95% RH (Non-condensing)
Operating Temperature:	-4°F to 158°F (-40°C to 70°C)

Appliance Replacement Parts Distributors

Appliance Replacement Parts Distributors

2014 SUPPLEMENT



2014 Supplement



HVAC/R & Test Instrument Catalog



Surge Protectors Warranty Registration Site



SUPCO International

